

Product datasheet

Specifications



SpaceLogic Controller I/O module, 8 analog voltage/current outputs, hand control/override switches

SXWAOV8HX10001

Main

Range	EcoStruxure Building Operation
Product name	I/O Modules
Device short name	AO-8-V-H
Product brand	Schneider Electric
Product or component type	I/O module

Complementary

Range compatibility	TB-IO-W1 terminal base
Analogue input type	Configurable voltage 0...10 V input voltage
Analogue output number	8
Control type	With integrated switch for off/on/automatic
Power consumption in W	0.7 W
Electrical connection	plug-in sub-base
[Us] rated supply voltage	24 V DC
Material	ABS/PC
Height	114 mm
Depth	64 mm
Width	90 mm
Net weight	156 g
Mounting support	DIN rail wall

Environment

Standards	UL 864 UL 916 FCC CFR 47 part 15
Product certifications	ICES-003 FCC part 15 class B CE RCM
Ambient air temperature for operation	0...50 °C
Ambient air temperature for storage	-20...70 °C

Relative humidity	0...95 %, non-condensing
IP degree of protection	IP20
Flame retardance	UL94V0-5VB

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	181.6 g
Package 1 Height	9 cm
Package 1 width	5.7 cm
Package 1 Length	11.7 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product