

Product datasheet

Specifications



SpaceLogic power supply module, 24 VAC or 21-30 VDC, for AS-P and I/O modules

SXWPS24VX10001

Main

Range	EcoStruxure Building Operation
Device short name	PS-24V
Product brand	Schneider Electric
Product or component type	Power supply module

Complementary

Range compatibility	AS-P controller TB-PS-W1 terminal base
Secondary power	10 W 24 V AC 10 W 21...30 V DC
Width	90 mm
Depth	64 mm
Height	114 mm
Quantity per set	1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	211.6 g
Package 1 Height	5.6 cm
Package 1 width	11.7 cm
Package 1 Length	9 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product
