

Product datasheet

Specifications



SpaceLogic Controller I/O module, 8 universal inputs, 4 analog voltage outputs

SXWUI8V4X10001

Main

Range	EcoStruxure Building Operation
Product name	I/O Modules
Device short name	UI-8/AO-V-4
Product brand	Schneider Electric
Product or component type	I/O module

Complementary

Input type	Universal
Product compatibility	Continuum Johnson Control Balco I/NET Xenta Satchwell Honeywell

Analogue input type	Configurable voltage, current or probe 0...20 mA Configurable voltage, current or probe 0...10 V input voltage Configurable voltage, current or probe 20 kOhm connection of probes Configurable voltage, current or probe 10 kOhm connection of probes Configurable voltage, current or probe 2.2 kOhm connection of probes Configurable voltage, current or probe 1.8 kOhm connection of probes Configurable voltage, current or probe 1 kOhm connection of probes Configurable voltage, current or probe 10 kOhm with shunt
---------------------	--

Analogue output number	4
Control type	Without
Material	ABS/PC
Height	114 mm
Depth	64 mm
Width	90 mm
Net weight	152 g

Environment

Standards	UL 864 UL 916 FCC CFR 47 part 15
-----------	--

Ambient air temperature for storage	-20...70 °C
-------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	169.6 g
Package 1 Height	5.7 cm
Package 1 width	11.7 cm
Package 1 Length	9.2 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product