

Produktdatablad

Spesifikasjoner



V311T/DN 50/Kv 38 - Seteventil 3veis interne gjenger

7311745000

EAN : 3606489658755

Teknisk informasjon

Valve product range	Venta
Produkt eller type komponent	Valve
Valve type	Globe
Valve product series	V311T
Valve model	V311T/50/38
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	3-Way
Valve connection type	Rp Internal
Valve connection size	Rp 2
Pipe size	50 mm
Body size	50 mm (2 in)
Flow characteristic	Equal percentage
Flow coefficient	43.94 cv 38 kvs
Trykkklasse	PN16
Operating fluid temperature	-20...120 °C
Pressure fluid max delta P normal life	399,90 kPa
Control valve rangeability	Greater than 50:1
Stroke length	20 mm
Seat leakage	Port A: Class IV-S1 (0.005 %)
Stem flow action	Stem up closes A and opens B to AB
Stem movement	Linear
Trim material	Brass
Materiale kropp	Nodular cast iron EN-JS 1030
Seat material	Port A: nodular cast iron EN-JS 1030 Port B: nodular cast iron EN-JS 1030
Stem material	Stainless steel AISI 303
Plug material	CW602N brass

Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A:EPDM (ethylene propylene diene monomer) Port B:EPDM (ethylene propylene diene monomer)
Packing material	EPDM (ethylene propylene diene monomer)
Gjeldende land	Europe Asia Pacific. Australia.

Forpakkingsinformasjon

Enhetsstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	4,219 kg
Forpakning 1 høyde	11 cm
Forpakning 1 bredde	18 cm
Forpakning 1 lengde	25 cm

Bærekraftig

EU RoHS-direktiv	Ikke gjeldende (Produktet inngår ikke i EUs RoHS direktivet)
Kinas RoHS-forskrift	Kinas RoHS-erklæring Produktet inngår ikke i Kinas RoHS-direktivet Stoffdeklarasjon til din informasjon
Miljøinformasjon	Produktmiljøprofil

Garantiperiode

Garanti	18 måneder
----------------	------------