

Product datasheet

Specifications



Valve 3Way Thread V341/15/1.6

7314121000

Main

Valve product range	Venta
Product or component type	Valve
Valve type	Globe
Valve product series	V341
Valve model	V341/15/1.6
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	3-Way
Valve connection type	G External
Valve connection size	G 1B
Pipe size	15 mm
Body size	15 mm (1/2 in)
Flow characteristic	Equal percentage
Flow coefficient	1.85 cv 1.6 kvs
Pressure class	PN16
Operating fluid temperature	-20...150 °C
Pressure fluid max delta P normal life	599.84 kPa
Control valve rangeability	Greater than 50:1
Stroke length	20 mm
Seat leakage	Port A: Less than 0.02 % of kvs (Ports A-AB) Port A: Less than 0.05 % of kvs (Ports B-AB)
Stem flow action	Stem up closes A and opens B to AB
Stem movement	Linear
Trim material	Stainless steel
Body material	Bronze Rg5
Seat material	Port A: stainless steel AISI 303 Port B: stainless steel AISI 303
Stem material	Stainless steel AISI 303

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Plug material	Stainless steel AISI 303
Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A:metal to metal
Packing material	EPDM (ethylene propylene diene monomer)
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.067 kg
Package 1 Height	5 cm
Package 1 width	10.5 cm
Package 1 Length	18 cm

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
-----------------	-----------