

Product datasheet

Specifications



M22 Electric Globe Valve Actuator, Modulating, 0-10 Vdc, 0-20 mAdc, 24 Vac, Terminal block, 2200 N, Linear, IP65

8900104000

Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	M22
Actuator model	M22
Product destination	globe valve
Actuator	Linear
Control type	Automatic reset
[Us] rated supply voltage	24 V AC 50 Hz - 15...10 %
Analogue input range	0...10 V 0...20 mA 2...10 V 4...20 mA
Power consumption in VA	15 VA AC
Hold-in power consumption in VA	15 VA AC
Power loss return	Non-spring return
Control signal	Proportional/modulating
Stroke length	50 mm
Stroke auto calibration	False
Electrical insulation class	Class II
Force N	2200 N
Force lbf	495 lbf
Position indicator	Stroke indicator on yoke
Leads and connections	Terminal block
Stroke running time	102 s
IP degree of protection	IP65
Duty cycle	80 %
Ambient air temperature for operation	-20...70 °C
Relative humidity	0...90 %
Ambient air temperature for storage	-20...70 °C

Targeted region	Europe Asia Pacific. Australia.
------------------------	---------------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7.75 kg
Package 1 Height	40 cm
Package 1 width	80 cm
Package 1 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
