

Product data sheet

Specifications



SpaceLogic PIBCV Actuator, Proportional/Floating, Spring Return, Normally Closed, 230 Vac, Terminal Block, 2000N, Linear, LED, IP54

MP2000-SRD-230

Main

Actuator product range	SmartX Actuator
Product or component type	Actuator
Actuator type	Electric
Actuator product series	MP2000-SR
Product destination	pressure independent control valves
Actuator	Linear
Control type	Automatic reset
Switch function	2 SPDT
[Us] rated supply voltage	230 V AC 50/60 Hz - 15...10 %
Analogue input range	0...10 V 2...10 V 0...20 mA 4...20 mA
Feedback signal	2...10 V DC 4...20 mA DC
Power loss return	Spring return
Control signal	Floating Proportional/modulating
Stroke length	50 mm
Stroke auto calibration	True
Electrical insulation class	Class II
Force N	2000 N
Force lbf	450 lbf
Position indicator	Stroke indicator on bracket
Additional features	LED status indicator
Conduit connection	Conduit connector holes
Leads and connections	Terminal block
Stroke running time	6 s
IP degree of protection	IP54
Ambient air temperature for operation	0...55 °C
Relative humidity	5...95 % non-condensing

Ambient air temperature for storage	-40...70 °C
--	-------------

Targeted region	Europe Asia Pacific. Australia.
------------------------	---------------------------------------

Packing Units

Package 1 Weight	9.600 kg
-------------------------	----------

Package 1 Height	41.800 cm
-------------------------	-----------

Package 1 width	20.800 cm
------------------------	-----------

Package 1 Length	20.100 cm
-------------------------	-----------

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
--------------------------	--

Mercury free	Yes
---------------------	-----

RoHS exemption information	Yes
-----------------------------------	---------------------

China RoHS Regulation	China RoHS declaration
------------------------------	--
