

Product data sheet

Specifications



SpaceLogic, Electric Actuator, Proportional, Non-Spring Return, 24 VAC, No leads, 2000 N, Linear, LED, IP54

MP2000

Main

Actuator product range	SmartX Actuator
Product or component type	Actuator
Actuator type	Electric
Actuator product series	MP2000
Actuator model	MP2000
Product destination	pressure independent control valves
Actuator	Linear
Control type	Automatic reset
Switch function	2 SPDT
Feedback signal	0...10 V DC 2...10 V DC
Power consumption in VA	9 VA AC
Power loss return	Non-spring return
Control signal	Proportional/modulating
Stroke length	40 mm
Stroke auto calibration	True
Electrical insulation class	Class III
Force N	2000 N
Force lbf	450 lbf
Position indicator	Stroke indicator on bracket
Additional features	LED status indicator
Conduit connection	Conduit connector holes
Leads and connections	Terminal block
Stroke running time	8 s
IP degree of protection	IP54
Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-40...70 °C
Targeted region	Europe Asia Pacific.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.8 kg
Package 1 Height	37.5 cm
Package 1 width	11.6 cm
Package 1 Length	15 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
