

Product datasheet

Specifications



EasyLogic CP 2% RH, Temp NTC 10K T3 - Duct Mounted, Analog

CP-AI-TH-SE-6200

Main

Range of product	EasyLogic
Product or component type	Humidity sensor Duct temperature sensor
Type of measurement	Temperature
Device application	Temperature control
IP degree of protection	IP65
Mounting support	Duct
Ambient air temperature for operation	-40...60 °C
Ambient air temperature for storage	-40...60 °C
Temperature measurement accuracy	+/- 0.2 °C at 25 °C
Device presentation	Complete device

Environment

Humidity setting range	0...100 %
Temperature setting range	-40...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.5 cm
Package 1 Width	11.8 cm
Package 1 Length	25 cm
Package 1 Weight	351 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) **83**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

[EU RoHS Directive](#) **Compliant with Exemptions**

REACH Regulation [REACH Declaration](#)

China RoHS Regulation [China RoHS declaration](#)

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **No**