

Product datasheet

Specifications



Temperature Sensor for SmartX IP Controllers LCD Display Setpoint Override - Cover included

SXWSATXXXSLX

Main

Range	SpaceLogic
Product or component type	Sensor
Product name	SmartX Living Space Sensor
Type of measurement	Temperature
Device application	HVAC Temperature control Fan speed controller
Product specific application	Cooling Heating
Product certifications	CE conforming to EN 61000-6-3 RCM EAC ICES-003
Display size	30 x 17 mm
Display type	LCD display
Information displayed	Temperature Operating mode Heating/cooling symbol
Flame retardance	UL94-V0
IP degree of protection	IP20
Location	Living space
Depth	24 mm
Height	115 mm
Width	85 mm
Ambient air temperature for operation	0...50 °C
Standards	UL 916 FCC part 15 class B
Colour	White
Relative humidity	0...95 %
Sensor type	Transmitter
Device presentation	Complete product
Surface finish	Matt
Local signalling	1 red, green and blue LED modulating , function: heating or air-conditioning application

Complementary

Communication port support	RJ45
Control type	+ button - button Present/absent symbol button
Material	ABS (acrylonitrile butadiene-styrene) GF10 FR
Function available	Override switches Setpoint adjustment
Max power consumption in W	2 W
Supply	Via bus connector
Range compatibility	EcoStruxure Building Operation SmartX Room Purpose Controller programmable controllers

Environment

Temperature setting range	0...50 °C
Measurement range	0...50 °C temperature

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	113 g
Package 1 Height	48 mm
Package 1 width	97 mm
Package 1 Length	140 mm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------